



HENGSHUI HUIYA NEW-MAT TECHNOLOGY CO., LTD

FLEXIBLE CHOKE KILL LINE

1、 Applicable to connection at locations when drill platform, semi-submersible drilling vessel or drilling vessel moves relatively and the installation dimensions of the drill rig subsequently change, and to delivery of oil, gas, mud and other high pressure media (including mainly relief line, blowout control line and choke kill line).



2、 The product features resistance to high pressure, thermal insulation, anti-flaming and fire resistance as well as inner wall with high abrasion resistance.



(full diameter consistent rubber hose)
Specification and basic parameters for flexible choke kill line

Technical Data

Inter dia.in mm(in)	Rated operating pressure in MPa(psi)	Test pressure in MPa(psi)	Min. burst pressure in MPa(psi)	Min. bending radius (mm)
50.8 (2)	35.0 (5 000)	70.0 (10 000)	105.0 (15 000)	900
64 (2 1/2)				1000
76.2 (3)				1000
89 (3 1/2)				1100
101.6 (4)				1200
50.8 (2)	70.0 (10 000)	105.0 (15 000)	157.5 (22 500)	1000
63.5 (2 1/2)				1100
76.2 (3)				1150
89 (3 1/2)				1200
101.6 (4)				1400
50.8 (2)	105.0 (15000)	157.5 (22500)	236.25 (33750)	1000
63.5 (2 1/2)				1150
76.2 (3)				1200
50.8 (2)	138.0 (20000)	207.0 (30000)	310.0 (45000)	900
64 (2 1/2)				1100
76.2 (3)				1200

Email: manager@huiyahose.com

Whatsapp/Wechat/Viber: +86 156 1084 1222

Manager: molly-ma

Technical Data